

Technical Data:

P-4021 MFP • P-4026w MFP • P-4027iw MFP

GENERAL		ENVIRONMENT		Interfaces	
Type	Desktop	Mains voltage	220/240 V, 50(60 Hz)	Network protocol	TCP/IP
Function	P-4021 MFP: Copy, print, scan P-4026w MFP/P-4027iw MFP: Copy, print, scan, fax	Power consumption	P-4021 MFP/P-4026w MFP: approx. 1,107 W max, approx. 574 W in operation, approx. 11 W in stand-by mode, approx. 0.4 W in sleep mode, TEC value: 0.35 kWh/week P-4027iw MFP: approx. 1,107 W max, approx. 574 W in operation, approx. 12 W in stand-by mode, approx. 0.4 W in sleep mode, TEC value: 0.35 kWh/week	Operating systems	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac OS 10.9
Print technology	Laser b/w	Noise level	approx. 50.2 dB(A) in operation, not measurable in stand-by mode (ISO 7779/9296)	Functions	Scan to SMB (version 3.0), Scan to E-Mail (SMTP), Scan to FTP, Scan to USB, TWAIN scan, WIA scan, SMTP authentication, LDAP, Multi Crop function*, eSCL support (ChromeOS scan, AirPrint and Mopria scan)
Original format	max A4 from platen glass	Safety	GS/TÜV, CE	FAX SYSTEM (P-4026w MFP / P-4027iw MFP)	
Original feeder	50 sheet document processor with simultaneous duplex scanning A6R-A4, 50-160 g/m ² (simplex/duplex)	PRINT SYSTEM		Compatibility	Super G3
Copy/print speed	40 A4 pages/min, duplex: max 20 A4 pages/min	Type	Integrated within the system	Original format	max A4
1st page (print/copy)¹	6.4 sec	Print format	A6R-A4	Modem speed	33.6 kbps
Warm-up time	P-4021 MFP/P-4026w MFP: 19 sec ¹ P-4027iw MFP: 29 sec ¹	Print resolution	600 x 600 dpi, max. 1,200 x 1,200 dpi (reduced speed)	Transmission speed	3 seconds or less using JBIG
Copy resolution	600 x 600 dpi	Processor	ARM Cortex-A9 dual core 1.2 GHz + ARM Cortex-M3 100 MHz	Compression method	JBIG, MMR, MR, MH
Greyscales	256	Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (1), SD-card slot, Wi-Fi ²	Fax resolution	Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi)
Paper feed	1 x 250 sheet universal cassette (A6R-A4), 100 sheet multi-bypass (A6R-A4 [min 70 x 148 mm, max 216 x 356 mm])	Network protocols	TCP/IP, Net BEUI	Fax memory	8 MB (6.75 MB image memory)
Paper weights	Universal cassette 60-163 g/m ² , multi-bypass 60-220 g/m ² , duplex 60-163 g/m ²	Operating systems	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac OS 10.9	Abbreviated dial	300 numbers
Paper output	150 sheets A4	Emulations	PCL6 (PCL 5c, XL), KPDLL 3 (PostScript 3 compatible), PRESCRIBE II, PDF 2.0, XPS	One touch dial	22/100 numbers (P-4026w MFP/P-4027iw MFP)
System memory	P-4021 MFP/P-4026w MFP: 1 GB RAM P-4027iw MFP: 2 GB RAM	Functions	USB direct printing, PDF/XPS direct printing, printing of e-mails, private printing, quiet mode (half speed mode), barcode printing, Mobile Print (Android/ iOS), Apple AirPrint, Universal print, WLAN as standard for P-4026w MFP and P-4027iw MFP	Group dial	50 numbers
Continuous copying	1-999 copies	SCAN SYSTEM		Operating systems	Windows 8/8.1/10/11, Server 2008/2008 R2/2012/2012 R2/2016/2019/2022, Linux, Chrome OS, Mac OS 10.9
Zoom	25 %-400 % in steps of 1 %	Scan type	CIS colour and b/w	Functions	Network fax driver, automatic redialling, delayed transmission
Display	P-4021 MFP/P-4026w MFP: LCD display 128 x 64 dots, half size 21 characters x 5 lines with numeric keypad P-4027iw MFP: Full color 4.3-inch LCD with pressure sensitive touch screen panel	Scan format	max A4	OPTIONS	
Functions	Duplex, job reservation, job programs, ID-card copy, continuous scan, skip blank pages, N-up-printing, login by function, 100 management codes, Secure Boot ³ , Runtime Integrity Check ³ , Simple Certificate Enrollment Protocol (SCEP), TLS 1.3, OCSP, CRL ⁴ , S/MIME ⁴ SIEM-Support, fax server interface etc.	Scan speed	b/w: max 40/80 A4 originals/min (simplex/duplex) with 300 dpi, colour: max 23/46 A4 originals/min (simplex/duplex) with 300 dpi	Paper feed	max 2x PF-1100 (250 sheet universal cassette [A6-A4, 60-163 g/m ²])
DIMENSIONS/WEIGHT		Scan resolution	200 dpi, 300 dpi, 400 dpi, 600 dpi	Other options	Card authentication kit (B), UG-33 ThinPrint [®] kit, UG-50 Trusted Platform Module, cabinet no. 78
Dimensions (H x W x D)	437 x 417 x 412 mm	Scan mode	Photo, text, photo/text, optimised for OCR	¹ depending on operating status	
Weight	approx. 19 kg	File types	TIFF, JPEG, PDF, PDF/A-2, high compression PDF, encrypted PDF, XPS, Open XPS	² optional	
				³ UG-50 Trusted Platform Module necessary	
				⁴ optional SD card memory required	








To enable HyPAS functionality additional memory is required. Specifications subject to change without notice. Image shows machine with optional accessories.

About UTAX: UTAX is a registered trademark of the TA Triumph-Adler GmbH. The Hamburg-based company specialises in the sale of high-quality printing and copying systems. The broad product portfolio includes hardware as well as software applications. In addition to copying, printing and multifunctional systems (MFP) for the office workplace, UTAX supplies customised IT solutions and services as well as comprehensive consulting for efficient document processes in companies. In Germany, the UTAX brand is distributed through a network of over 200 authorised dealers. Internationally, the company operates in over 40 countries in the EMEA region.

IF IT WORKS, IT'S



utax.com

UTAX

07/2025